



NOTE

- POWER WIRE : 2.5SQ BLACK
- CONTROL WIRE(AC) : 1.5SQ RED
- CONTROL WIRE(DC) : 1.5SQ BLUE
- EARTH WIRE : 2.5SQ GREEN

MOROT SPEC.

- HOIST : 3φ 0.75kW 4P
- TROLLEY : 3φ 0.4kW 4P

DYNAMIC BRAKE RESISTOR SPEC.

- ULH60 40Ω

INVERTER SPEC.

- HOIST
SOHO 15NC02Y [200-230V]
SOHO 15NC04Y [380-460V]
- TROLLEY
SOHO 15NC02Y [200-230V]
SOHO 15NC04Y [380-460V]

ABBREVIATION

CT : CURRENT TRANSFORMER
MCCB : MOLDED CASE CIRCUIT BREAKER
DBR : DYNAMIC BRAKING RESISTOR
TP : THERMAL PROTECTOR
EM : EMERGENCY
RD : RED
BK : BLACK
WT : WHITE
GR : GREEN
YL : YELLOW

TITLE				SHEET	
EDLM-125,250,490,500KG				1/1	
1Phase 220V 50/60Hz				REVISION NO	
3Phase 220,380,440,460V 50/60Hz				2	
ONE PCB CIRCUIT DIAGRAM				DRAWING NO	
DRAWING	CHECKED	REVIEWED	APPROVED		
S.W			Y.K	EDLM001E06	
21.10.29			21.10.29		

DAESAN InoTEC INC.